



Carbonair's LPC series carbon vessels are ideal for low cost applications. The materials used in construction are in accordance with standards established by AWWA, FDA, and EPA.

## Specifications\*



Model	LPC 3	LPC 3.85
Flow Range (gpm)	1 - 10	1 - 13
Carbon Capacity (lb)	200	250
Vessel Diameter	2'-1"	2'-6"
Vessel Height	3'-0"	3'-6"
Bed Area (ft <sup>2</sup> )	2.7	3.7
Empty Weight (lb)	50	100
Loaded Weight (lb)	250	350
Operating Weight (lb)	423	725
Spent & Drained Weight (lb)	355	600
Design Pressure (psig)	10	5
Influent Connection (NPT)	1"	1.5"
Effluent Connection (NPT)	1"	1.5

### Design Features

- Drums meet UN standards
- Baked enamel exterior
- Epoxy-phenolic interior lining

### Options

- Influent/effluent sample and pressure taps
- Influent/effluent quick-connect couplings
- Flexible interconnecting hose
- External sample/gauge ports
- Piping packages
- Flow instrumentation
- Complete line of granular activated carbon and other media

### Service Centers

**FLORIDA**  
4710 Dignan Street  
Jacksonville, FL 32254  
800.241.7833  
904.387.4465  
904.387.5058 Fax

**MINNESOTA**  
7500 Boone Ave N #101  
Brooklyn Park, MN 55428  
800.526.4999  
763.315.4771  
763.315.4614 Fax

**TEXAS**  
4889 Hunter Rd. Bldg 1-C  
San Marcos, TX 78666  
800.893.5937  
512.392.0085  
512.392.0066 Fax

**VIRGINIA**  
4003 West Main Street  
Salem, VA 24153  
800.204.0324  
540.380.5913  
540.380.5920 Fax